

#	Layer	Thickness	Description	Dk	Df	Note
	Top Solder	0.015mm	Soldermask IPC-SM840	3,5	0,028	used on rigid parts
1	Top Side	0.045mm	ED Copper + plating			
		0.220mm	Prepreg IPC-4101/127/128	4,3	0,011	FR-4.1 filled, halogen free
2	Inner Layer 1	0.017mm	ED Base Copper			
		0.410mm	Core IPC-4101/127/128	4,8	0,011	FR-4.1 filled, halogen free
3	Inner Layer 2	0.017mm	ED Base Copper			
		0.220mm	Prepreg IPC-4101/127/128	4,3	0,011	FR-4.1 filled, halogen free
4	Inner Layer 3	0.017mm	ED Base Copper			
		0.410mm	Core IPC-4101/127/128	4,8	0,011	FR-4.1 filled, halogen free
5	Inner Layer 4	0.017mm	ED Base Copper			
		0.220mm	Prepreg IPC-4101/127/128	4,3	0,011	FR-4.1 filled, halogen free
6	Inner Layer 5	0.017mm	ED Base Copper			
		0.410mm	Core IPC-4101/127/128	4,8	0,011	FR-4.1 filled, halogen free
7	Inner Layer 6	0.017mm	ED Base Copper			
		0.220mm	Prepreg IPC-4101/127/128	4,3	0,011	FR-4.1 filled, halogen free
8	Bottom Side	0.045mm	ED Copper + plating			
	Bottom Solder	0.015mm	Soldermask IPC-SM840	3,5	0,028	used on rigid parts
Total thickness: 2.332mm						

notes:

Final copper thickness according to IPC-6012

Please regard to our sectional design rules:
▶ www.we-online.com

BASIC8_ML8_2,33_17

PCB Thickness Tolerance: ± 10%

customer	created
pcb name	approved
engineer	format
date	A4, landscape

Template Revision: 07/2020 by Andreas Schilpp / Michael Kress / Werner Öchslen

